



Arcade Bicycle Basin

US-BICY1

Installation Instructions

Place the bicycle against the wall to determine the height of the basin, remembering to include the height of the shelf.

Fix the basin to the wall using Fischer bolts (not supplied). Do not overtighten the fixings as the basin will need to be removed to fit the shelf.

Mark the position of the shelf underneath the basin, ensuring that the center of the cut-out is centered on the basin.

Remove the basin from the wall to fit the shelf.

Mark the locations of the shelf fixings on the wall and screw the fixings into the wall.

Note: The stud on the wall fixings are off-center so that the shelf height can be adjusted using a spanner.

Insert a small amount of silicone sealant into the pre-drilled holes and slide the shelf into place.

Fit the basin and the bike.

Using the height adjuster on the bike's seat post. Lift the bracket to the underside of the shelf and screw through into the bottom of the shelf (fixings not supplied). Once the bracket is attached to the shelf, tighten the allen key on the bike's seat post.

Shelf Care

The shelf is made from solid oak and polished with Danish Oil. Due to the nature of this real wood product, variations in the grain are to be expected. Standing water left on the shelf may cause staining. Remove any water with a soft cloth. Do not spray with any polish or wax. Being a natural product, it will require very occasional re-application of clear Danish oil (use very sparingly).