

MPRO 1701 THERMOSTATIC VALVE ROUGH AND TRIM SET WITH VOLUME CONTROL/DIVERTER AND INTEGRATED HANDSHOWER

Polished Chrome 1.75 GPM

US-PRO1701RSETC

FEATURES

- MPRO combines iconic definition with versatile style and superb functionality
- Single integrated volume control/diverter for 2 water outlets
- Standard backplate includes icons indicating Shower and Bathtub
- Optional backplate with icons for Shower and Handshower is available separately (US-PRO1738)
- Set includes rough valve and trim with handshower
- Trim includes a hose and elbow which are required for installation and must be on site for installation
- Rough features Vernet thermostatic cartridge
- The thermostatic valve senses and controls the actual water temperature and blends hot water with cold water to ensure constant, safe temperatures, preventing scalding.

SPECIFICATIONS

Finish	Polished Chrome
Extension kit	US-EK101525C
Barcode	5055833663262
Number of water outlets	2
Handle style	Lever
Flow rate	11 GPM
Inlet connection size	3/4" NPT
Outlet connection size	3/4" NPT
Water pressure minimum	20 PSI
Water pressure maximum	Operating pressure of 60 PSI and static pressure of 144 PSI
Installation type	Concealed
IAPMO	Yes
Rough-in depth minimum	3"
Rough-in depth maximum	4"
Handshower flow rate	1.75 GPM



✓ Limited lifetime. Commercial



AVAILABLE COLOR/FINISHES

Color	SKU	Description
	US-PRO1701RSETC	Polished Chrome
	US-PRO1701RSETV	Satin Nickel
	US-PRO1701RSETMB	Matte Black
	US-PRO1701RSETBB	Brushed Brass

MPRO Horizontal Thermostatic Valve Trim
US-PRO1701
US-PRO1701175

