

DIAL CENTRAL 2001 THERMOSTATIC VALVE TRIM WITH TWO INTEGRATED VOLUME CONTROLS AND HANDSHOWER

US-DIAL-CENT-12C

FEATURES

- Dial couples intuitive, precise control with effortless performance
- 2 integrated volume controls for 2 water outlets
- Required rough features Vernet thermostatic cartridge
- The thermostatic valve senses and controls the actual water temperature and blends hot water with cold water to ensure constant, safe temperatures, preventing scalding.
- Required rough (sold separately): US-DL2001R

FEATURES

- Due to water restriction laws, this product may not be eligible for purchase in your area. Please check with your plumbing professional for further information.



✔ Limited lifetime. Commercial

SPECIFICATIONS

Barcode	0
Finish	Polished Chrome
Number of water outlets	2
Handle style	Round
Flow rate	13 GPM
Inlet connection size	3/4" NPT
Outlet connection size	3/4" NPT
Water pressure minimum	20 PSI
Water pressure maximum	Operating pressure of 60 PSI and static pressure of 144 PSI
Rough-in depth minimum	2-7/8"
Rough-in depth maximum	3-5/8"
Extension kit	Not available
Installation type	Concealed
Notes	Due to water restriction laws, this product may not be eligible for purchase in your area. Please check with your plumbing professional for further information.

Dial Central 2001 Horizontal Thermostatic Valve Trim
US-DIAL-CENT-12C

